# DHG V Diaphragm Wall Hydraulic Grab



## DHG V - Variety with value

Global market conditions have seen changes which have affected every aspect of a successful job site. There has been a focus on increased efficiency and cost savings, one result of which has been a trend for contractors to move from using mechanical grabs to hydraulic diaphragm wall grabs. The hydraulic grab comes out in the lead in terms of trench accuracy and ease of operation.

With the DHG V, Bauer designed a grab with the accuracy of a hydraulic grab and the strength and freefall abilities of a mechanical grab.

This new grab system is available in a range of sizes and configurations to satisfy the wide range of applications and challenges our customers on the front lines are facing worldwide.



turning device

- Grab weight can be optimized to all hook loads
- Optimized flow resistance in the trench
- Stronger grab body & shovel set
- Larger bushings & bearings
- Multiple length, width and weight options
- Huge weight range with just one grab body
- A single grab type for multiple applications

Length: Width: Hydraulic cylinder: Weight: No. of steering flaps: 2,400 – 4,200 mm 120, 180 t 15 – 35 t



DHG V with 12 flaps



- Annex set
- 2 Turning device
- 3 Steering flap 4

1

- Cylinder 5
- Thrust rod 6 Extension
- Cutting edge 7
- 8 Shovel set
- Chiseling device 9
- Control shovel 10
- position (optional) 11 Gyroscopic compass (optional)

## **Spotlights**

#### Cylinder force

- Hydraulic cylinder forces range from 1,200 kN to 1,800 kN
- A simple mounting system allows for quick and easy cylinder exchange





## Additional weights

Additional weights of different sizes can be added if necessary, directly distributing additional weight into the trestle.

## Cleaner and chiseling device

Customers can select either a cleaning or chiseling system for installation in the shovel, and can later switch between the two functions by changing trestle.





**Cutting edge or stop end removing aid** Simple exchange between these two options is possible.

#### **Deviation control**

The grab module for B-Tronic system was developed for monitoring the verticality of diaphragm wall trenches continuously during excavation. The current position of the grab is transferred and displayed online during the excavation. An inclinometer is built into the grab to measure the inclination of the trench in the x- and y-axis.

Data transfer from the grab to the operator's cab is carried out via a heavy-duty electrical cable which, by following every move of the grab, is automatically reeled on and off by a hydraulically operated cable recoil system. Data are visualized on a touch-screen monitor. The measured values can be stored, evaluated and printed by using a PC. A final measurement of deviation of the trench is carried out by a separate survey of the trench after the completion of excavation.



Optional: Additionally the DHG V can be equipped with a gyroscope and a distance measurement of the grab cylinder. So the deviation on z-axis and the actual shovel position can be displayed on the B-Tronic screen to support of the operator.





## Turning device TD 4

Turning device TD 4 can be installed in all grabs with a minimum body thickness of 600 mm.

The hydraulically operated rotating device increases manoeuvrability when working on corner panels or in confined areas. Productivity in hard soil and verticality is also improved as the negative influence of asymmetric teeth arrangement is compensated by turning the grab at 180°.



TD 4 in 90°



**TD 4 in 25°** 

#### Teeth

Various tooth options are available for maximum effectiveness in a wide range of soil conditions.



## **Technical Data**

## Width Definition

**Two grab size standards are available** Size variation is demonstrated on a basis of the 600 mm trench grab, with measurement variation applying to all models.

Standard 1: Teeth: 630 mm Shovel: 600 mm

Standard 2: Teeth: 600 mm Shovel: 580 mm



## **Grab Body Extensions**

Width extension sets can be used in conjunction with different shovel sizes to increase trench width.

**Length extension sets** can be used to extend a 2,400 mm grab body to 2,800 mm, the 2,400 and 2,800 mm grab bodies to 3,200 mm as well as the 2,800 mm grab body to 4,200 mm.

560





DHG V 1,200 x 2,800 mm

DHG V 600 x 2,800 mm

#### DHG V 600 x 3,200 mm

Special lengths and widths available on demand.

1

2

3



DHG V 2,400 mm – weight table (in tonnes)							
Width (mm)	600	800		1000	1200	1500	
Volume (m <sup>3</sup> )	0.57	0.8	32	1.07	1.32	1.70	
Weight of soil fill	1.14	1.64		2.14	2.64	3.40	
Basic grab weight	13.91	14.8	39	16.18	17.34	18.39	
8 flaps	1.66	2.21		2.29	2.46	2.63	
Weight with filling, 8 flaps and TD 4	17.63	19.66		21.53	23.36	25.34	
Options							
Chiseling		0.78		0.87	1.12	1.16	
Upgrade to heavy trestle		1.41		1.52	2.00	2.62	
Further options – valid for all trench widths:							
Upgrade to heavy rod	0.80		Upgrade to 180 t cylinder		er	0.54	
X-axis flaps	0.83	TC		TD 4		0.92	
BAUER end stop removing aid	0.43						

## **Technical Data**

## 2,800 mm Trench Length





if grab body is based on 2.40 m = + 0.85 tonnes

DHG V 2,800 mm – weight table (in tonnes)						
Width (mm)	600	800	)	1000	1200	1500
Volume (m <sup>3</sup> )	0.73	1.0	)4	1.36	1.68	2.15
Weight of soil fill	1.46	2.0	9	2.72	3.35	4.30
Basic grab weight	14.67	15.5	2	17.10	18.26	19.30
8 flaps	1.66	2.2	!1	2.29	2.46	2.63
Weight with filling, 8 flaps and TD 4	18.71	20.74		23.03	24.99	27.15
Options						
Chiseling		0.7	'8	0.87	1.12	1.16
Upgrade to heavy trestle		1.4	1	1.52	2.00	2.62
Further options – valid for all trench widths:						
Upgrade to heavy rod	0.80		Upgrade to 180 t cylinder			0.54
X-axis flaps	0.83		TD 4			0.92

0.43

BAUER end stop removing aid





if grab body is based on 2.40 m = + 0.35 tonnes

DHG V 3,200 mm – weight table (in tonnes)						
Width (mm)	600	800		1000	1200	1500
Volume (m <sup>3</sup> )	0.88	1.25		1.63	2.01	2.57
Weight of soil fill	1.76	2.50		3.26	4.02	5.14
Basic grab weight	16.42	18.8	88	18.73	20.35	21.53
8 flaps	1.66	2.21		2.29	2.46	2.63
Weight with filling, 8 flaps and TD 4	20.76	24.51		25.20	27.75	30.22
Options						
Chiseling		0.78		0.87	1.12	1.16
Upgrade to heavy trestle		1.4		1.52	2.00	2.62
Further options - valid for all trenc	h widths:					
Upgrade to heavy rod	0.80		Upgrade to 180 t cylinder		er	0.54
X-axis flaps	0.83		TD 4			0.92
BAUER end stop removing aid	0.48					

## 4,200 mm Trench Length



DHG V 4,200 mm – weight table (in tonnes)						
Width (mm)	600	800	1000	1200	1500	
Volume (m <sup>3</sup> )	1.38	1.95	2.54	3.12	4.00	
Weight of soil fill	2.76	3.90	5.08	6.24	8.00	
Basic grab weight	19.00	20.12	21.58	22.98	24.13	
8 flaps	1.66	2.21	2.29	2.46	2.63	
Weight with filling, 8 flaps and TD 4	24.34	27.15	29.87	32.60	35.68	
Options						
Chiseling		0.78	0.87	1.12	1.16	
Upgrade to heavy trestle		1.41	1.52	2.00	2.62	
Chiseling Upgrade to heavy trestle		0.78 1.41	0.87 1.52	1.12 2.00	1.16 2.62	

Further options – valid for all trench widths:						
Upgrade to heavy rod	0.80	Upgrade to 180 t cylinder	0.54			
X-axis flaps	0.83	TD 4	0.92			
BAUER end stop removing aid	0.58					

## Impressions







**Global Network** 



Service





Equipment

Training

International Service Hotline +800 1000 1200\* (freecall) +49 8252 97-2888 BMA-Service@bauer.de

\* Where available







BAUER Maschinen GmbH BAUER-Strasse 1 86529 Schrobenhausen Germany Tel. +49 8252 97-0 bma@bauer.de www.bauer.de

Design developments and process improvements may require the specification and materials to be updated and changed without prior notice or liability. Illustrations may include optional equipment and not show all possible configurations. These and the technical data are provided as indicative information only, with any errors and misprints reserved.