

OLIN ENGINEERING, INC

15622 COMPUTER LN HUNTINGTON BEACH, CA 92649 PH 714 897 1230 F 714 892 9268

WWW.OLINPUMP.COM INFO@OLINPUMP.COM



SPECIFICATIONS 5 70 1/2" MINUS PUMP

OUTPUT: cmh/cyh	56/73
DELIVERY PRESSURE: bar/psi	77/1100
DELIVERY CYLINDER: mm/inch	152/6
STROKE: mm/inch	610/24
STROKES/MINUTE:	86
ENGINE POWER: kw/hp	54/74
ENGINE TORQUE: nm/lb ft	400/295
HOPPER CAPACITY: cu mtr/cu ft	.17/6
OUTLET: mm/inch	100/4
OIL COOLER	YES
CONTROL SYSTEM:	ELECTRIC/HYDRAULIC
HYDRAULIC CAPACITY: l/gal	321/85
WEIGHT: kg/lbs	2372/5230

The 5 70 is the newest edition to OLIN's Ball Valve line, a hybrid of the 5 60 and 5 80, combining 6" material cylinders for lean mixes, 3-1/2" hydraulic cylinders for structural mixes, and 4.4 liters of DEF free JCB torque. Residential or commercial, simple, dependable hydraulics and Millennium manifold mean consistent, reliable revenue every day. Go with the leader in small line pumps, OLINPUMP.

* All OLIN Ball Valve pumps feature del'y system pressure release valve standard



CONCRETE - GROUT - SHOTCRETE